

# Smart Power Sensor



## 🎯 Accurate



- Measurement accuracy > class 1 within full temperature range

## 📄 Simple & Easy

- Standard din-rail mounting of DIN 35 mm
- Small volume, 1P2W 36 mm, 3P4W 72 mm
- LCD display, convenient for users to set and check
- Coupling connection for installation
- CT and RS485 cables included in accessories

## ✅ Energy-efficient

- Overall power consumption  $\leq 1$  W

Technical Specification	DDSU666-H	DTSU666-H
<b>General Specification</b>		
Dimension (H * W * D)	36 * 100 * 65.5mm (1.4 * 3.9 * 2.6 inch)	72 * 100 * 65.5 mm (2.8 * 3.9 * 2.6 inch)
Mounting type	DIN35 Rail	
Weight (including cables)	1.2 kg (2.6 lb)	1.5 kg (3.3 lb)
<b>Power Supply</b>		
Power grid type	1P2W	3P4W
Input power (phase voltage)	176 Vac ~ 288 Vac	
Power consumption	$\leq 0.8$ W	$\leq 1$ W
<b>Measurement Range</b>		
Line voltage	/	304 Vac ~ 499 Vac
Phase voltage	176 Vac ~ 288 Vac	
Current	0 ~ 100A	
<b>Measurement Accuracy</b>		
Voltage	$\pm 0.5\%$	
Current / Power / Energy	$\pm 1\%$	
Frequency	$\pm 0.01$ Hz	
<b>Communication</b>		
Interface	RS485	
Baud rate	4800 / 9600 bps	
Communication protocol	Modbus-RTU	
<b>Environment</b>		
operating temperature range	-25 °C ~ 60 °C	
Storage temperature range	-40 °C ~ 70 °C	
Operating humidity range	5% ~ 95% (non-condensing)	
<b>Others</b>		
Accessories	RS485 Cable (10m / 33 ft.)	
	1 CT 100A / 40mA (6m / 19 ft.) 	3 CT 100A / 40mA (6m / 19 ft.) 

The text and figures reflect the current technical state at the time of printing. Subject to technical changes. Errors and omissions excepted. Huawei assumes no liability for mistakes or printing errors. For more information, please visit solar.huawei.com. Version No.:05-(20180627)